

P20/P21/C10 FLUORESCENT LIGHT DATA SHEET

TYPE

- Double tube fluorescent fitting.
- P20 - Zone 2,21&22
- P21- Zone 21&22
- C10 - IP65

LAMP TYPE

- Bi-pin T8 Fluorescent tubes.

MOUNTING

- Two stainless steel mounting brackets that clip onto the back of the polycarbonate housing.
- Additional stainless steel hanging clips for catenary cable hanging.

SPECIAL EX FEATURES

- Emergency battery back-up option available.

ELECTRICAL SPECIFICATIONS

- Input voltage is 230, 50Hz.
- Electronic driver
- PFC > 0.95
- 4 Foot tube: 2 x 36W

CERTIFICATION

- Ex ec IIC T5 Gc
- Ex tb IIIC T135Db
- MASC S/23-2313X



ORDER INFORMATION

PART NUMBER	DESCRIPTION	MAT. NUMBER
• ZONE 2, 21 & 22 FITTING		
AMP20-237	4ft, Ex ec, Ex t,	
AMP20-259	5ft, Ex ec, Ex t	
• ZONE 21 & 22 FITTING		
AMP21-237	4ft, Ex t	
AMP21-259	5ft, Ex t	
• STANDARD IP65 FITTINGS		
AMC10-237	4ft,	
AMC10-237-E2	4Ft, 20% Battery emergency	
AMC10-237-E1	4Ft, 100% Battery emergency	
AMC10-259	5ft	
AMC10-259-E2	5ft, 20% Battery emergency	
AMC10-259-E1	5ft, 100% Battery emergency	



PLEASE NOTE:
DUE TO TECHNICAL VARIANCES AND CHANGING TECHNOLOGY DETAILS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

Electroflame (PTY) LTD
Design | Manufacture | Supply
Ex Equipment

