



Electroflame (PTY) LTD

Design | Manufacture | Supply
Ex Equipment



Surface

Levelite MK3

Application

The Levelite MK3 is an LED tube fixture fitting suitable for Zone 1, 2, 21 & 22 areas.

Construction

The housing consists of a transparent polycarbonate tube with aluminium end caps attached at each end. One end cap is closed off while the other has a lid with a M20 cable entry. A slotted steel mounting bracket is attached along the length of the fitting and includes various mounting options.

The fitting can be fitted with one, two or three LED strips which give a 120, 240 and 360 degree beam spread respectively. (The 360 degree beam will have a section of light obscured by the bracket)

The fitting comes in three standard lengths to replace the older, traditional 2, 4 and 5 foot fluorescent fittings. There is an optional transparent clear protective clip-over sleeve that can be supplied.



Certification

- Ex db IIC T4 Gb
- Ex tb IIIC T1350C dB IP65
- IA Number: MASC S/21-2498X

Electrical Specification

- 100 to 230 VAC
- 740 mm fitting: 16 W. (2 foot)
- 1350 mm length fitting 25 W. (4 foot)
- 1650 mm length fitting 30W. (5 foot)

(Wattages and lengths may vary depending on application)

Order Information

One x LED Strip Fittings

- 740 mm fitting (2 foot)
- 1350 mm fitting (4 foot)
- 1650 mm fitting (5 foot)

Part Number

AMLL3-201
AMLL3-401
AMLL3-501

Two x LED Strip Fittings

- 740 mm fitting (2 foot)
- 1350 mm fitting (4 foot)
- 1650 mm fitting (5 foot)

Part Number

AMLL3-202
AMLL3-402
AMLL3-502

Three x LED Strip Fittings

- 740 mm fitting (2 foot)
- 1350 mm fitting (4 foot)
- 1650 mm fitting (5 foot)

Part Number

AMLL3-203
AMLL3-403
AMLL3-503