

P24/C14 LED STRIP LIGHT

TYPE

Weatherproof LED strip linear light.

CONSTRUCTION

- Polycarbonate housing.
- Defrosted polycarbonate cover.
- Low profile polycarbonate captive clips.

EX LAMP TYPE

- Vossloh-Schwabe LED pcb strips.
- 5000K (4000 and 6000K available on request)

MOUNTING

- Two stainless steel mounting brackets that clip onto the back of the polycarbonate housing.
- Additional stainless steel hanging clips for catenary cable hanging.



ELECTRICAL SPECIFICATIONS

- Input voltage is 100 - 277VAC, 50/60Hz.
- PFC > 0.95
- 4 Foot single strip: 1 x 45W
- 4 Foot double strip: 2 x 33W (Total 66W)
- 5 Foot single strip: 1 x 56W
- 5 Foot double strip: 2 x 36W (Total 72W)

CERTIFICATION

- Ex ec mc IIC TG Gc
- Ex tb IIIC T85°C Db IP65
- IA No: MASC S/22-2316X

ORDER INFORMATION

PART NUMBER	DESCRIPTION	MAT. NUMBER
• ZONE 2, 21 & 22 FITTING		
AMP24-410	4ft Single, Ex ec, Ex t	
AMP24-420	4ft Double, Ex ec, Ex t	
• ZONE 21 & 22 FITTING		
AMP24-710	4ft Single, Ex t	
AMP24-720	4ft Double, Ex t	
• STANDARD IP65 FITTINGS		
AMC14-237	4ft, Double standard fitting	
AMC14-237-E2	4Ft, 20% Battery emergency	
AMC14-237-E1	4Ft, 100% Battery emergency	



PLEASE NOTE:
DUE TO TECHNICAL VARIANCES AND CHANGING TECHNOLOGY DETAILS ARE
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

Electroflame (PTY) LTD

Design | Manufacture | Supply
Ex Equipment

